

TXGT 60

Artikkelnummer: 520.19.1011.2

EAN: 5703347532474



Spesifikasjoner

Minimum luftstrøm [m ³ /h]	282
Minimum lydeffekt [dB(A)]	52
Maksimal luftstrøm [m ³ /h]	487
Maksimal lydeffekt [dB(A)]	65
Betjening	Glas touch
Materiale	Rustfritt stål



Aftrækstilbehør

Navn	Antall	Price
Carbon Flex Filter	535.46.1000.9	3 485,00 kr
Mini Plasmex	535.21.1500.9	6 965,00 kr
Thermex Plasmex® filter I - Rund	535.10.1000.9	10 440,00 kr
Spenningsbånd 8 60-215	815.16.8208.9	275,00 kr
Avtrekksett Ø 160 mm	830.51.2162.9	1 125,00 kr
fleksibel slange. Ø 162 mm per meter	800.70.4162.9	405,00 kr
Slangesett Ø160 1,2 meter	800.70.6160.9	755,00 kr
Lyd- og kondensisolert flexslange Ø 162 mm	810.16.5160.9	1 045,00 kr
Avtrekksett - lyd/kondensisolert Ø162 mm	830.51.6162.9	2 045,00 kr
Resirkulasjonsfilter	535.19.3600.9	360,00 kr

Thermex Link

Navn	Antall	Price
Safemex komfyrvakt - 1 fase	536.06.1000.0	12 105,00 kr
Thermex Trigger Link-modul	536.99.1000.9	2 660,00 kr
Thermex Plasmex® Smart Link-modul	536.99.1150.9	5 010,00 kr