

Decor 840 900 mm Rustfri

Artikkelnummer: 528.23.8498.2

EAN: 5703347531507

A

Spesifikasjoner

Minimum luftstrøm [m ³ /h]	290
Minimum lydeffekt [dB(A)]	54
Maksimal luftstrøm [m ³ /h]	540
Maksimal lydeffekt [dB(A)]	66
Luftmengde boost [m ³ /t]	750
Volum ved boost [dB(A)]	70
Betjening	Glas touch
Materiale	Rustfritt stål



Aftrækstilbehør

Navn	Antall	Price
Thermex Plasmex® filter I - Rund	535.10.1000.9	10 440,00 kr
Mini Plasmex	535.21.1500.9	6 965,00 kr
fleksibel slange. Ø 162 mm per meter	800.70.4162.9	405,00 kr
Carbon Flex Filter	535.46.1000.9	3 485,00 kr
Lyd- og kondensisolert flexslange Ø 162 mm	810.16.5160.9	1 045,00 kr
Strekkbånd 6 60-165 mm	815.16.8206.9	195,00 kr
Avtrekksett Ø 160 mm	830.51.2162.9	1 125,00 kr
Slangesett pvc ø162 mm	800.70.7160.9	1 005,00 kr
Slangesett Ø160 1,2 meter	800.70.6160.9	755,00 kr
Avtrekksett - lyd/kondensisolert Ø162 mm	830.51.6162.9	2 045,00 kr

Thermex Link

Navn	Antall	Price
Thermex Trigger Link-modul	536.99.1000.9	2 660,00 kr
Prolink Basic II	536.99.1501.9	6 150,00 kr
Prolink Plasmex II	536.99.1503.9	16 085,00 kr
Prolink Premium II	536.99.1505.9	13 135,00 kr
Thermex Top Link Module II	536.99.1300.9	10 368,75 kr
Safemex komfyrvakt - 1 fase	536.06.1000.0	12 105,00 kr
Thermex Plasmex® Smart Link-modul	536.99.1150.9	5 010,00 kr